



Onyx Counter-Top POU Cooler



507-ONYXCT

Black Hot/Cold Temp Counter-Top

Power

Voltage	115V
Frequency (Hz)	60 Hz
Power Consumption	4.85A / 547W / 115V
Cold Power Consumption	1.5A / 109W / 115V
Hot Power Consumption	3.7A / 449W / 115V
ES (kWh/24 hrs.)	0.754
% lower than ES Standard	14%

Hot Water System

Avg. Hot Water Temp at Nozzle @75°F Ambient (Before/After On)	176°F / 190°F
Hot Water ARI Rating	45, 6 oz > 165°F +/- 10%
Hot Thermostat / Heat Limiter	202°F
Hot Thermostat / Thermister Cycle	140°F - 198°F
Hot Water Flow Rate	1.24 oz/sec
Hot Tank Size (Liter)	1.4L

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Before/After On)	42°F / 48°F
Cold Water ARI Rating	24, 5 oz < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°F / -8°F
Cold Water Flow Rate	1.35 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.55

Weights and Measurements

Net Weight (Lbs)	30 lbs
Gross Weight (Lbs)	38.4 lbs
Cooler Dimensions WxDxH (inch)	12.5 x 14 x 17 7/8
Container Load (20')	340
Container Load (40')	700
Certifications	UL Listed